



Druckrohre für Abwasser Wavin TS-Abwasserdruckentsorgung

Wavin TS Abwasser • SDR 17 • in geraden Längen

d mm	s mm	L* m	kg/ m	Stange je Pal.	Meter je Pal.
250	14,8	12	11,0	11	132
280	16,6	12	13,7	11	132
315	18,7	12	17,4	8	96
355	21,1	12	22,1	8	96
400	23,7	12	28,0	5	60
450	26,7	12	35,4	4	48

* Sonderlängen auf Anfrage. (Standardlängen 6/12 m)



Wavin TS Abwasser • SDR 11 • in geraden Längen


d mm	s mm	L* m	kg/ m	Stange je Pal.	Meter je Pal.
63**	5,8	12	1,050	132	1.584
75**	6,8	12	1,470	102	1.224
90	8,2	12	2,120	58	696
110	10,0	12	3,140	48	576
125	11,4	12	4,080	34	408
140	12,7	12	5,080	38	456
160	14,6	12	6,670	20	240
180	16,4	12	8,420	17	204
200	18,2	12	10,400	14	168
225	20,5	12	13,100	14	168
250	22,7	12	16,200	11	132
280	25,4	12	20,300	11	132
315	28,6	12	25,600	8	96
355	32,2	12	32,500	8	96
400	36,3	12	41,300	5	60
450	40,9	12	52,300	4	48

* Sonderlängen auf Anfrage. (Standardlängen 6/12 m)

** Vollwandrohre aus XSC 50.

Wavin TS Abwasser • SDR 11 • in Ringbunden

d mm	s mm	L* m/Bund	kg/ Bund	A mm	B mm	H mm
63**	5,8	100	105,00	2.090	1.750	410
75**	6,8	100	147,00	2.290	1.750	413
90	8,2	100	212,00	2.890	2.400	495
110	10,0	100	314,00	3.000	2.400	605
125	11,4	100	408,00	3.080	2.400	688
140	12,7	100	508,00	3.165	2.400	770
160	14,6	100	667,00	3.270	2.400	1200
180	16,4	100	842,00	3.384	2.400	990



* Sonderlängen auf Anfrage.

** Vollwandrohre aus XSC 50.