


Steckmuffen-Maße

Abmessung DN	d mm	t* mm	D (PN 10) mm	D (PN 16) mm
50	63	96	85	–
65	75	101	101	–
80	90	106	119	123
100	110	114	142	147
125	140	125	174	183
150	160	134	200	208
200	225	158	274	285
250	280	179	339	352
300	315	191	372	394
400	450	234	534	–

* Mindesteinstecktiefe


Druckrohre mit Steckmuffen • PN 10 und eingelegten 3-S-Ringen



Abmessung DN	d mm	s mm	L m	Gewicht kg/m
50	63	3,0	6	0,85
65	75	3,6	6	1,22
80	90	4,3	6	1,75
100	110	5,3	6	2,61
125	140	6,7	6	4,18
150	160	7,7	6	5,47
200	225	10,8	6	10,80
250	280	13,4	6	16,60
300	315	15,0	6	20,90
400	450	21,5	6	42,70

Nach DIN 8062, Reihe 4 und DIN 19532, PN 10/20°C

Druckrohre mit Steckmuffen • PN 16 und eingelegten 3-S-Ringen



Abmessung DN	d mm	s mm	L m	Gewicht kg/m
80	90	6,7	6	2,61
100	110	8,2	6	3,90
125	140	10,4	6	6,27
150	160	11,9	6	8,17
200	225	16,7	6	16,10
250	280	20,8	6	24,90
300	315	23,4	6	31,50

Nach DIN 8062, Reihe 5 und DIN 19532, PN 10/20°C