



PVC-Steckmuffenbögen 11°-90° PN 10 MK-RS/MQ-RS 3-S-Ringe eingelegt Fabrikat Wavin



Abmessung DN	Grad mm	R mm	Z mm	Gewicht kg/Stk.
300	11	1103	232	28,90
300	22	1103	340	27,00
300	30	1103	421	31,40
300	45	1103	583	39,55
300	90	1103	1229	55,00
400	11	1575	332	84,74
400	22	1575	486	98,12
400	30	1575	602	102,58
400	45	1575	832	120,42

DN 80 - DN 300 auch in PN 16 lieferbar


PVC-Druckrohre mit Klebemuffen PN 10/16 Fabrikat Wavin



PN 10

Abmessung DN	d mm	s mm	L m	Gewicht kg/m
50	63	3,0	6	0,854
65	75	3,6	6	1,220
80	90	4,3	6	1,750
100	110	5,3	6	2,610
125	140	6,7	6	4,180
150	160	7,7	6	5,470
200	225	10,8	6	10,800

Nach DIN 8062, Reihe 4 und DIN 19532, PN 10/20°C



PN 16

Abmessung DN	d mm	s mm	L m	Gewicht kg/m
50	63	4,7	6	1,290
65	75	5,6	6	1,820
80	90	6,7	6	2,610
100	110	8,2	6	3,900
150	160	11,9	6	8,170

Nach DIN 8062, Reihe 4 und DIN 19532, PN 10/20°C